

INSPECTION REPORT



For the Property at:

XYZ

TORONTO, ON

Prepared for: MRS. XYZ

Inspection Date: Saturday, June 24, 2017

Prepared by: Ardi Honarmand



Competent Home Inspection
2885 Bayview Avenue
Toronto, ON M2K 0A3
647-521-8224

www.competenthomeinspection.com
competenthomeinspection@gmail.com



July 7, 2017

Dear Mrs. XYZ,

RE: Report No. 1004, v.0
XYZ
Toronto, ON

Thanks very much for choosing us to perform your home inspection. The inspection itself and the attached report comply with the requirements of the Standards of Practice of our Association (InterNACHI). This document defines the scope of a home inspection.

Clients sometimes assume that a home inspection will include many things that are beyond the scope. We encourage you to read the Standards of Practice included as an appendix to this report, so that you clearly understand what things are included in the home inspection and report.

The report has been prepared for the exclusive use of our client. No use by third parties is intended. We will not be responsible to any parties for the contents of the report, other than the party named herein .

The report is effectively a snapshot of the house, recording the conditions on a given date and time. Home inspectors cannot predict future behavior, and as such, we cannot be responsible for things that occur after the inspection. If conditions change, we are available to revisit the property and update our report.

The report itself is copyrighted, and may not be used in whole or in part without our express written permission.

Again, thanks very much for choosing us to perform your home inspection.

Sincerely,

Ardi Honarmand
on behalf of
Competent Home Inspection

Competent Home Inspection
2885 Bayview Avenue
Toronto, ON M2K 0A3
647-521-8224
www.competenthomeinspection.com
competenthomeinspection@gmail.com

SUMMARY

XYZ, Toronto, ON June 24, 2017

Report No. 1004, v.0

www.competenthomeinspection.com

SUMMARY

ROOFING

EXTERIOR

STRUCTURE

ELECTRICAL

HEATING

COOLING

INSULATION

PLUMBING

INTERIOR

APPENDIX

Note: For the purpose of this report the building is considered to be facing **South**.

This Summary outlines potentially significant issues from a cost or safety standpoint. This section is provided as a courtesy and cannot be considered a substitute for reading the entire report. Please read the complete document;

[Priority Maintenance Items](#)

This concludes the Summary section.

The remainder of the report describes each of the home's systems and also details any recommendations we have for improvements. Limitations that restricted our inspection are included as well.

The suggested time frames for completing recommendations are based on the limited information available during home inspection. These may have to be adjusted based on the findings of specialists.

[Home Improvement - ballpark costs](#)


Description

Sloped roofing material:

- [Asphalt shingles](#)



1. Asphalt shingles



2. Asphalt shingles

Probability of leakage: • Low

Limitations

Inspection performed: • With binoculars • From the ground

EXTERIOR

XYZ, Toronto, ON June 24, 2017

Report No. 1004, v.0

www.competenthomeinspection.com

SUMMARY

ROOFING

EXTERIOR

STRUCTURE

ELECTRICAL

HEATING

COOLING

INSULATION

PLUMBING

INTERIOR

APPENDIX

Description

Gutter & downspout material: • [Aluminum](#)

Gutter & downspout discharge:

- [Above grade](#)



3. Above grade




4. Above grade

Lot slope: • [Away from building](#) • [Flat](#)

Wall surfaces - masonry:

- [Brick](#)



5. Brick

Driveway:

- Asphalt



6. Asphalt

Porch:

- Concrete



7. Concrete

Limitations

Exterior inspected from: • Ground level


Recommendations


ROOF DRAINAGE \ Downspouts

1. Condition: • [Should discharge 6 feet from building](#)

Implication(s): Chance of water damage to contents, finishes and/or structure

Task: For information only (no tasks required)





WALLS \ Flashings and caulking

2. Condition: • All masonry that is adjoining the house or building that is subject to movement due to freezing and thawing, should have a caulked/flexible sealant in their joint. This is to help prevent water penetration.

Task: Seal the gap with heavy duty flexible caulking (i.e. Dymonic by Tremco)

Cost: Minor



8.

3. Condition: • [Caulking missing or ineffective](#)

All exterior wall penetrations should be caulked with a flexible sealant to prevent penetration of moisture, drafts, rodents and insects.

Implication(s): Chance of water damage to contents, finishes and/or structure

Task: For information only

WALLS \ Brick, stone and concrete

4. Condition: • Do not fill/parge these weeping holes as they are for water drainage.



9.


PORCHES, DECKS, STEPS, PATIOS AND BALCONIES \ Handrails and guards

5. Condition: • [Spindles \(balusters\) missing](#)

Implication(s): Fall hazard

Task: Provide

Cost: Minor



10. Spindles (balusters) missing

LANDSCAPING \ Driveway

6. Condition: • [Cracked or damaged surfaces](#)

Implication(s): Trip or fall hazard

Task: Replace the driveway with new granular base, hot mix asphalt pavement in two lifts (HL3 & HL8) with proper slope, and below grade weeping tile for drainage if needed. Follow the current City of Toronto standard T-310.050 attached to end of this report.

Time: When remodelling

EXTERIOR

XYZ, Toronto, ON June 24, 2017

Report No. 1004, v.0

www.competenthomeinspection.com

SUMMARY

ROOFING

EXTERIOR

STRUCTURE

ELECTRICAL

HEATING

COOLING

INSULATION

PLUMBING

INTERIOR

APPENDIX

Cost: about \$3,000



11. Cracked, settled, or damaged surfaces



12. 4" drop at garage entrance

Description

Configuration: • [Basement](#)

Foundation material: • [Poured concrete](#)

Floor construction:

- [Joists](#)



13. Joists

Exterior wall construction: • [Wood frame / Brick veneer](#)

Roof and ceiling framing:

- [Trusses](#)



14. Trusses

SUMMARY

ROOFING

EXTERIOR

STRUCTURE

ELECTRICAL

HEATING

COOLING

INSULATION

PLUMBING

INTERIOR

APPENDIX

Limitations

Percent of foundation not visible: • 95 %

Recommendations

FOUNDATIONS \ Foundation

7. Condition: • [Cracked](#)

Implication(s): Chance of water damage to contents, finishes and/or structure | Weakened structure

Location: Exterior - right side of the building (north face)

Task: Monitor

Description

Service entrance cable and location:


- [Underground - cable material not visible](#)



15. Underground - cable material not visible

Service size:

- [200 Amps \(240 Volts\)](#)



16. 200 Amps (240 Volts)

Main disconnect/service box rating:


- [100 Amps](#)




17. 100 Amps

Main disconnect/service box type and location:

- [Breakers - basement](#)




18. Breakers - basement



19. Breakers - basement



20. Breakers - basement



21. Breakers - basement

Distribution wire material and type: • [Copper - non-metallic sheathed](#)

Type and number of outlets (receptacles): • [Grounded - typical](#)

Smoke detectors: • NOTE: SMOKE & CO DETECTORS TO BE TESTED BY THE HOMEOWNER.

****It is recommended to have a smoke detector and carbon monoxide detector on each floor, to check the date to make sure they are not expired [less than 10 years] and change batteries/make sure they are working.

Limitations

Inspection limited/prevented by: • The home inspection includes only a sampling check of wiring, lights, and receptacles etc.

Recommendations

DISTRIBUTION SYSTEM \ Outlets (receptacles)

8. Condition: • [No GFCI/GFI \(Ground Fault Circuit Interrupter\)](#)

It is recommended to have all plugs, exterior and within 3' of a sink [basin of water] should have working GFI's

Implication(s): Electric shock

Location: Throughout

Task: Provide

Time: less than a year

Cost: less than \$200


Ground fault interrupter

the GFI circuitry within the outlet checks constantly for a difference between the current in the black and white wires

if there is a difference (even as little as 5 milliamps), there is a current leak (possibly through your body) and the GFI shuts down the receptacle and other receptacles downstream

note:

if the GFI is in the panel, the entire circuit will be shut down





22. No GFCI/GFI (Ground Fault Circuit...

DISTRIBUTION SYSTEM \ Smoke detectors

9. Condition: • It is recommended to have a smoke detector on each floor, to check the date to make sure they are not expired [less than 10 years] and change batteries/make sure they are working.

DISTRIBUTION SYSTEM \ Carbon monoxide (CO) detectors

10. Condition: • It is recommended to have a CO detector on each floor, to check the date to make sure they are not expired [less than 10 years] and change batteries/make sure they are working.

Description

System type:

- [Furnace](#)



23. Furnace

Fuel/energy source: • [Gas](#)

Furnace manufacturer: • Bryant

Heat distribution: • [Ducts and registers](#)

Approximate capacity: • [95,000 BTU/hr](#)

Efficiency: • [High-efficiency](#)

Approximate age: • [20 years](#)

Typical life expectancy: • Furnace (high efficiency) 15 to 20 years

Main fuel shut off at:

- Meter



24. Meter

Limitations

Safety devices: • Not tested as part of a building inspection

Heat loss calculations: • Not done as part of a building inspection

Heat exchanger: • Not visible

Recommendations

GAS FURNACE \ Life expectancy

11. Condition: • [Near end of life expectancy](#)

It is recommended to have the furnace and ducts inspected by a certified technician.

Implication(s): Equipment failure | No heat for building

Task: Inspect/service

Time: Immediate

Description

Air conditioning type:

- [Air cooled](#)



25. Air cooled

Manufacturer: • Keeprite

Cooling capacity: • [2 Tons](#)

Compressor approximate age: • 2 years

Typical life expectancy: • 12 to 15 years

Failure probability: • [Low](#)

Limitations

Heat gain calculations: • Not done as part of a building inspection

Description

Attic/roof insulation material:

- [Glass fiber](#)



26. Glass fiber

Attic/roof insulation amount/value: • [R-32](#)

Attic/roof air/vapor barrier: • [Plastic](#)

Attic/roof ventilation:

- [Roof vent](#)



27. Roof vent (view from exterior)

- [Soffit vent](#)



28. Roof vent (view from the attic)

INSULATION AND VENTILATION

XYZ, Toronto, ON June 24, 2017

Report No. 1004, v.0

www.competenthomeinspection.com

SUMMARY

ROOFING

EXTERIOR

STRUCTURE

ELECTRICAL

HEATING


COOLING

INSULATION

PLUMBING

INTERIOR

APPENDIX



29. Soffit vent (view from exterior)



30. Soffit vent (view from the attic)



31. 3D view of soffit & roof vent (for info)

Limitations

Attic inspection performed: • From access hatch

Recommendations


ATTIC/ROOF \ Hatch

12. Condition: • [Not weatherstripped](#)

If the attic access hatch is not properly sealed/closed/weatherstripped, moisture from the living room escapes through the hatch creating condensation, drip stains, and possibly mold on the hatch frame.

Implication(s): Chance of condensation damage to finishes and/or structure | Increased heating and cooling costs

Task: Provide weatherstripping. Also, check the black stain on the hatch frame for mold for piece of mind, and if mold exists, remove it, or replace the framing.





32. Drip stain, maybe mold?


ATTIC/ROOF \ Roof vents

13. Condition: • [Inadequate](#)

The attic ventilation MAY BE insufficient. Homeowners to note that lack of ventilation or excessive moisture can lead to deterioration of roof sheathing and air quality problems (i.e. mold).

Implication(s): Chance of condensation damage to finishes and/or structure

Task: This can be easily investigated by an expert roofing contractor.



INSULATION AND VENTILATION

XYZ, Toronto, ON June 24, 2017

Report No. 1004, v.0

www.competenthomeinspection.com

SUMMARY

ROOFING

EXTERIOR

STRUCTURE

ELECTRICAL

HEATING

COOLING

INSULATION

PLUMBING

INTERIOR

APPENDIX



33.

Description

Water supply source: • Public

Service piping into building: • [Copper](#)

Supply piping in building: • [Copper](#)

Main water shut off valve at the:

• Basement

located in mechanical room (furnace room)



34. Basement

Water heater type:

• [Induced draft](#)



35. Induced draft

Water heater fuel/energy source: • [Gas](#)

Water heater manufacturer: • Bradford White



36.

Tank capacity: • 50 gallons

Water heater approximate age: • 4 years

Typical life expectancy: • 12 years or more


Limitations

Items excluded from a building inspection: • Water quality • Concealed plumbing • Tub/sink overflows • The performance of floor drains or clothes washing machine drains

Description

Major floor finishes:

- [Carpet](#)



37. Carpet

Major wall and ceiling finishes: • [Plaster/drywall](#)

Windows: • [Fixed](#) • [Sliders](#) • [Casement](#)

Glazing: • [Double](#)

Limitations

Not included as part of a building inspection: • Carbon monoxide detectors, security systems, central vacuum



Recommendations

GARAGE \ Door between garage and living space

14. Condition: • [No self closer](#)

Implication(s): Hazardous combustion products entering home

Task: Provide



38. No self closer

END OF REPORT

APPENDIX

XYZ, Toronto, ON June 24, 2017

Report No. 1004, v.0

www.competenthomeinspection.com

SUMMARY

ROOFING

EXTERIOR

STRUCTURE

ELECTRICAL

HEATING


COOLING

INSULATION


PLUMBING

INTERIOR

APPENDIX



ASPHALT DRIVEWAY



CONCRETE DRIVEWAY

TYPE OF DRIVEWAY		PAVEMENT STRUCTURE	THICKNESS (mm)
ASPHALT	RESIDENTIAL	HL-3 F (FINE) TOP (2 LIFTS)	80
		HL-8 BASE (SEE NOTE 2)	0
		GRANULAR A	150
	INDUSTRIAL, CONDOMINIUM HIGH RISE, COMMERCIAL	HL-3 F (FINE) TOP	50
		HL-8 BASE (2 LIFTS)	80
		GRANULAR A	150
CONCRETE	RESIDENTIAL	PORTLAND CEMENT CONCRETE (PCC) TOP	150
		GRANULAR A	150
	INDUSTRIAL CONDOMINIUM HIGH RISE, COMMERCIAL	PORTLAND CEMENT CONCRETE (PCC) TOP	180
		GRANULAR A	150

NOTES:

1. KEY BEHIND CURB TO BE LOWERED TO ACCOMMODATE THE FULL DRIVEWAY THICKNESS.
2. NEW ASPHALT DRIVEWAY TO BE PLACED IN 2 LIFTS WITH 40 mm HL-3 TOP AND 40 mm HL-8 BASE, OR AS SPECIFIED.

All dimensions are in millimetres unless otherwise shown.



ENGINEERING & CONSTRUCTION SERVICES STANDARD DRAWING

REV 2

NOV 2014

DRIVEWAY THICKNESS

T-310.050-8

NTS

SHEET 1

The International Standards of Practice for Performing a General Home Inspection

and

The International Code of Ethics for Home Inspectors



www.NACHI.org

Effective June 2013

InterNACHI's Vision and Mission

InterNACHI, the International Association of Certified Home Inspectors, is [the world's largest organization of residential and commercial property inspectors](#).

As a [federally tax-exempt, 501\(c\)\(6\) non-profit](#), InterNACHI provides [training, certification, and Continuing Education](#) for its membership, including property inspectors, licensed real estate agents, and building contractors; and provides for its membership [business training, software products, marketing services](#), and [membership benefits](#).

InterNACHI members follow a comprehensive [Standards of Practice](#) and are bound by a strict [Code of Ethics](#). The membership takes part in the regular exchange of professional experiences and ideas to support each other. InterNACHI maintains an [industry blog](#), [Inspection Forum](#), and [local Chapters](#) in support of this exchange of information. InterNACHI provides its members with other means of direct and membership-wide communication to further their understanding of their particular roles in the inspection industry and how best to serve their clients. The benefits of this cross-communication enhance the members' ability to build their businesses and develop specialized ancillary services.

In fulfilling this fundamental objective of training and mentoring its inspector-members, InterNACHI's broader mission is to educate homeowners by helping them understand the functions, materials, systems and components of their properties. InterNACHI inspectors are committed to providing consistent, accessible and trusted information to their clients about their properties' condition.

Headquarters:

International Association of Certified Home Inspectors (InterNACHI)
1750 30th Street
Boulder, CO 80301
USA

(303) 502-6214
fastreply@internachi.org
U.S. DUNS #015117501

To find an InterNACHI Certified Professional Inspector®, visit InspectorSeek.com.

Irrevocable Non-Exclusive License for Use by Government Entities

The International Association of Certified Home Inspectors (InterNACHI) hereby grants this irrevocable, non-exclusive, royalty-free license to any federal, state, or local government located in the United States or Canada, and any agencies thereof, including licensing boards, to use InterNACHI's Standards of Practice, Code of Ethics, and any other materials found on the InterNACHI website (www.nachi.org) free of charge, without the need for pre-approval, provided that each use is clearly attributed to InterNACHI.

InterNACHI specifically authorizes any government or government agency to use and copy, for any public purpose, InterNACHI's Standards of Practice, Code of Ethics, and other materials without further approval from InterNACHI, even if the materials are protected by copyright or other laws.

Available Online in English, Spanish and French

The International Standards of Practice for Performing a General Home Inspection is available online at <http://www.nachi.org/sop.htm>

The International Code of Ethics for Home Inspectors is available online at http://www.nachi.org/code_of_ethics.htm

Estándares de Práctica, the Spanish version of the International Standards of Practice for Performing a General Home Inspection, is available online at <http://www.nachi.org/sopspanish.htm>

Código de ética, the Spanish version of the International Code of Ethics for Home Inspectors, is available online at <http://www.nachi.org/coespanish.htm>

Les Normes de Pratique Internationales pour la Réalisation d'une Inspection Générale de Biens Immobiliers, the French version of the International Standards of Practice for Performing a General Home Inspection, is available online at <http://www.nachi.org/res-sop-french.htm>

Code de Déontologie de l'Inspection Immobilière, the French version of the International Code of Ethics for Home Inspectors, is available online at <http://www.nachi.org/code-of-ethics-french.htm>

*InterNACHI's International Standards of Practice for Performing a General Home Inspection***The International Standards of Practice for
Performing a General Home Inspection****TABLE OF CONTENTS**

1. Definitions and Scope	3
2. Limitations, Exceptions & Exclusions	3
3. Standards of Practice	5
3.1. Roof	5
3.2. Exterior	5
3.3. Basement, Foundation, Crawlspace & Structure	6
3.4. Heating	6
3.5. Cooling	7
3.6. Plumbing	7
3.7. Electrical	8
3.8. Fireplace	9
3.9. Attic, Insulation & Ventilation	10
3.10. Doors, Windows & Interior	11
4. Glossary of Terms	12
Code of Ethics	14

1. Definitions and Scope

1.1. A general home inspection is a non-invasive, visual examination of the accessible areas of a residential property (as delineated below), performed for a fee, which is designed to identify defects within specific systems and components defined by these Standards that are both observed and deemed material by the inspector. The scope of work may be modified by the Client and Inspector prior to the inspection process.

- I. The general home inspection is based on the observations made on the date of the inspection, and not a prediction of future conditions.
- II. The general home inspection will not reveal every issue that exists or ever could exist, but only those material defects observed on the date of the inspection.

1.2. A material defect is a specific issue with a system or component of a residential property that may have a significant, adverse impact on the value of the property, or that poses an unreasonable risk to people. The fact that a system or component is near, at, or beyond the

end of its normal, useful life is not, in itself, a material defect.

1.3. A general home inspection report shall identify, in written format, defects within specific systems and components defined by these Standards that are both observed and deemed material by the inspector. Inspection reports may include additional comments and recommendations.

2. Limitations, Exceptions & Exclusions**2.1. Limitations:**

- I. An inspection is not technically exhaustive.
- II. An inspection will not identify concealed or latent defects.
- III. An inspection will not deal with aesthetic concerns or what could be deemed matters of taste, cosmetic defects, etc.
- IV. An inspection will not determine the suitability of the property for any use.
- V. An inspection does not determine the market value of the property or its marketability.
- VI. An inspection does not determine the insurability of the property.
- VII. An inspection does not determine the advisability or inadvisability of the purchase of the inspected property.
- VIII. An inspection does not determine the life expectancy of the property or any components or systems therein.
- IX. An inspection does not include items not permanently installed.
- X. This Standards of Practice applies only to properties with four or fewer residential units and their attached garages and carports.

2.2. Exclusions:

- I. The inspector is not required to determine:
 - A. property boundary lines or encroachments.
 - B. the condition of any component or system that is not readily accessible.
 - C. the service life expectancy of any component or system.
 - D. the size, capacity, BTU, performance or efficiency of any component or system.
 - E. the cause or reason of any condition.
 - F. the cause for the need of correction, repair or replacement of any system or component.
 - G. future conditions.
 - H. compliance with codes or regulations.

InterNACHI's International Standards of Practice for Performing a General Home Inspection

- I. the presence of evidence of rodents, birds, animals, insects, or other pests.
 - J. the presence of mold, mildew or fungus.
 - K. the presence of airborne hazards, including radon.
 - L. the air quality.
 - M. the existence of environmental hazards, including lead paint, asbestos or toxic drywall.
 - N. the existence of electromagnetic fields.
 - O. any hazardous waste conditions.
 - P. any manufacturers' recalls or conformance with manufacturer installation, or any information included for consumer protection purposes.
 - Q. acoustical properties.
 - R. correction, replacement or repair cost estimates.
 - S. estimates of the cost to operate any given system.
- II. The inspector is not required to operate:
- A. any system that is shut down.
 - B. any system that does not function properly.
 - C. or evaluate low-voltage electrical systems, such as, but not limited to:
 - 1. phone lines;
 - 2. cable lines;
 - 3. satellite dishes;
 - 4. antennae;
 - 5. lights; or
 - 6. remote controls.
 - D. any system that does not turn on with the use of normal operating controls.
 - E. any shut-off valves or manual stop valves.
 - F. any electrical disconnect or over-current protection devices.
 - G. any alarm systems.
 - H. moisture meters, gas detectors or similar equipment.
- III. The inspector is not required to:
- A. move any personal items or other obstructions, such as, but not limited to: throw rugs, carpeting, wall coverings, furniture, ceiling tiles, window coverings, equipment, plants, ice, debris, snow, water, dirt, pets, or anything else that might restrict the visual inspection.
 - B. dismantle, open or uncover any system or component.
 - C. enter or access any area that may, in the inspector's opinion, be unsafe.
 - D. enter crawlspaces or other areas that may be unsafe or not readily accessible.
 - E. inspect underground items, such as, but not limited to: lawn-irrigation systems, or underground storage tanks (or indications of their presence), whether abandoned or actively used.
 - F. do anything that may, in the inspector's opinion, be unsafe or dangerous to him/herself or others, or damage property, such as, but not limited to: walking on roof surfaces, climbing ladders, entering attic spaces, or negotiating with pets.
 - G. inspect decorative items.
 - H. inspect common elements or areas in multi-unit housing.
 - I. inspect intercoms, speaker systems or security systems.
 - J. offer guarantees or warranties.
 - K. offer or perform any engineering services.
 - L. offer or perform any trade or professional service other than general home inspection.
 - M. research the history of the property, or report on its potential for alteration, modification, extendibility or suitability for a specific or proposed use for occupancy.
 - N. determine the age of construction or installation of any system, structure or component of a building, or differentiate between original construction and subsequent additions, improvements, renovations or replacements.
 - O. determine the insurability of a property.
 - P. perform or offer Phase 1 or environmental audits.

InterNACHI's International Standards of Practice for Performing a General Home Inspection

- Q. inspect any system or component that is not included in these Standards.

- I. perform a water test.

- J. warrant or certify the roof.

- K. confirm proper fastening or installation of any roof-covering material.

3. Standards of Practice

3.1. Roof

- I. The inspector shall inspect from ground level or the eaves:

- A. the roof-covering materials;
- B. the gutters;
- C. the downspouts;
- D. the vents, flashing, skylights, chimney, and other roof penetrations; and
- E. the general structure of the roof from the readily accessible panels, doors or stairs.

- II. The inspector shall describe:

- A. the type of roof-covering materials.

- III. The inspector shall report as in need of correction:

- A. observed indications of active roof leaks.

- IV. The inspector is not required to:

- A. walk on any roof surface.
- B. predict the service life expectancy.
- C. inspect underground downspout diverter drainage pipes.
- D. remove snow, ice, debris or other conditions that prohibit the observation of the roof surfaces.
- E. move insulation.
- F. inspect antennae, satellite dishes, lightning arresters, de-icing equipment, or similar attachments.
- G. walk on any roof areas that appear, in the inspector's opinion, to be unsafe.
- H. walk on any roof areas if doing so might, in the inspector's opinion, cause damage.

3.2. Exterior

- I. The inspector shall inspect:

- A. the exterior wall-covering materials, flashing and trim;
- B. all exterior doors;
- C. adjacent walkways and driveways;
- D. stairs, steps, stoops, stairways and ramps;
- E. porches, patios, decks, balconies and carports;
- F. railings, guards and handrails;
- G. the eaves, soffits and fascia;
- H. a representative number of windows; and
- I. vegetation, surface drainage, retaining walls and grading of the property, where they may adversely affect the structure due to moisture intrusion.

- II. The inspector shall describe:

- A. the type of exterior wall-covering materials.

- III. The inspector shall report as in need of correction:

- A. any improper spacing between intermediate balusters, spindles and rails.

- IV. The inspector is not required to:

- A. inspect or operate screens, storm windows, shutters, awnings, fences, outbuildings, or exterior accent lighting.
- B. inspect items that are not visible or readily accessible from the ground, including window and door flashing.
- C. inspect or identify geological, geotechnical, hydrological or soil conditions.

InterNACHI's International Standards of Practice for Performing a General Home Inspection

- D. inspect recreational facilities or playground equipment.
- E. inspect seawalls, breakwalls or docks.
- F. inspect erosion-control or earth-stabilization measures.
- G. inspect for safety-type glass.
- H. inspect underground utilities.
- I. inspect underground items.
- J. inspect wells or springs.
- K. inspect solar, wind or geothermal systems.
- L. inspect swimming pools or spas.
- M. inspect wastewater treatment systems, septic systems or cesspools.
- N. inspect irrigation or sprinkler systems.
- O. inspect drainfields or dry wells.
- P. determine the integrity of multiple-pane window glazing or thermal window seals.

- C. observed indications of possible foundation movement, such as sheetrock cracks, brick cracks, out-of-square door frames, and unlevel floors; and
- D. any observed cutting, notching and boring of framing members that may, in the inspector's opinion, present a structural or safety concern.

IV. The inspector is not required to:

- A. enter any crawlspace that is not readily accessible, or where entry could cause damage or pose a hazard to him/herself.
- B. move stored items or debris.
- C. operate sump pumps with inaccessible floats.
- D. identify the size, spacing, span or location or determine the adequacy of foundation bolting, bracing, joists, joist spans or support systems.
- E. provide any engineering or architectural service.
- F. report on the adequacy of any structural system or component.

3.3. Basement, Foundation, Crawlspace & Structure

I. The inspector shall inspect:

- A. the foundation;
- B. the basement;
- C. the crawlspace; and
- D. structural components.

II. The inspector shall describe:

- A. the type of foundation; and
- B. the location of the access to the under-floor space.

III. The inspector shall report as in need of correction:

- A. observed indications of wood in contact with or near soil;
- B. observed indications of active water penetration;

3.4. Heating

I. The inspector shall inspect:

- A. the heating system, using normal operating controls.

II. The inspector shall describe:

- A. the location of the thermostat for the heating system;
- B. the energy source; and
- C. the heating method.

III. The inspector shall report as in need of correction:

- A. any heating system that did not operate; and
- B. if the heating system was deemed inaccessible.

IV. The inspector is not required to:

- A. inspect or evaluate the interior of flues or chimneys, fire chambers, heat exchangers, combustion air systems, fresh-air intakes,

InterNACHI's International Standards of Practice for Performing a General Home Inspection

humidifiers, dehumidifiers, electronic air filters, geothermal systems, or solar heating systems.

- B. inspect fuel tanks or underground or concealed fuel supply systems.
- C. determine the uniformity, temperature, flow, balance, distribution, size, capacity, BTU, or supply adequacy of the heating system.
- D. light or ignite pilot flames.
- E. activate heating, heat pump systems, or other heating systems when ambient temperatures or other circumstances are not conducive to safe operation or may damage the equipment.
- F. override electronic thermostats.
- G. evaluate fuel quality.
- H. verify thermostat calibration, heat anticipation, or automatic setbacks, timers, programs or clocks.

3.5. Cooling

- I. The inspector shall inspect:
 - A. the cooling system, using normal operating controls.
- II. The inspector shall describe:
 - A. the location of the thermostat for the cooling system; and
 - B. the cooling method.
- III. The inspector shall report as in need of correction:
 - A. any cooling system that did not operate; and
 - B. if the cooling system was deemed inaccessible.
- IV. The inspector is not required to:
 - A. determine the uniformity, temperature, flow, balance, distribution, size, capacity, BTU, or supply adequacy of the cooling system.
 - B. inspect portable window units, through-wall units, or electronic air filters.
 - C. operate equipment or systems if the exterior temperature is below 65° Fahrenheit, or when

other circumstances are not conducive to safe operation or may damage the equipment.

- D. inspect or determine thermostat calibration, cooling anticipation, or automatic setbacks or clocks.
- E. examine electrical current, coolant fluids or gases, or coolant leakage.

3.6. Plumbing

- I. The inspector shall inspect:
 - A. the main water supply shut-off valve;
 - B. the main fuel supply shut-off valve;
 - C. the water heating equipment, including the energy source, venting connections, temperature/pressure-relief (TPR) valves, Watts 210 valves, and seismic bracing;
 - D. interior water supply, including all fixtures and faucets, by running the water;
 - E. all toilets for proper operation by flushing;
 - F. all sinks, tubs and showers for functional drainage;
 - G. the drain, waste and vent system; and
 - H. drainage sump pumps with accessible floats.
- II. The inspector shall describe:
 - A. whether the water supply is public or private based upon observed evidence;
 - B. the location of the main water supply shut-off valve;
 - C. the location of the main fuel supply shut-off valve;
 - D. the location of any observed fuel-storage system; and
 - E. the capacity of the water heating equipment, if labeled.
- III. The inspector shall report as in need of correction:

InterNACHI's International Standards of Practice for Performing a General Home Inspection

- A. deficiencies in the water supply by viewing the functional flow in two fixtures operated simultaneously;
 - B. deficiencies in the installation of hot and cold water faucets;
 - C. mechanical drain stops that were missing or did not operate if installed in sinks, lavatories and tubs; and
 - D. toilets that were damaged, had loose connections to the floor, were leaking, or had tank components that did not operate.
- IV. The inspector is not required to:
- A. light or ignite pilot flames.
 - B. measure the capacity, temperature, age, life expectancy or adequacy of the water heater.
 - C. inspect the interior of flues or chimneys, combustion air systems, water softener or filtering systems, well pumps or tanks, safety or shut-off valves, floor drains, lawn sprinkler systems, or fire sprinkler systems.
 - D. determine the exact flow rate, volume, pressure, temperature or adequacy of the water supply.
 - E. determine the water quality, potability or reliability of the water supply or source.
 - F. open sealed plumbing access panels.
 - G. inspect clothes washing machines or their connections.
 - H. operate any valve.
 - I. test shower pans, tub and shower surrounds or enclosures for leakage or functional overflow protection.
 - J. evaluate the compliance with conservation, energy or building standards, or the proper design or sizing of any water, waste or venting components, fixtures or piping.
 - K. determine the effectiveness of anti-siphon, back-flow prevention or drain-stop devices.
 - L. determine whether there are sufficient cleanouts for effective cleaning of drains.
 - M. evaluate fuel storage tanks or supply systems.
 - N. inspect wastewater treatment systems.
 - O. inspect water treatment systems or water filters.
 - P. inspect water storage tanks, pressure pumps, or bladder tanks.
 - Q. evaluate wait time to obtain hot water at fixtures, or perform testing of any kind to water heater elements.
 - R. evaluate or determine the adequacy of combustion air.
 - S. test, operate, open or close: safety controls, manual stop valves, temperature/pressure-relief valves, control valves, or check valves.
 - T. examine ancillary or auxiliary systems or components, such as, but not limited to, those related to solar water heating and hot water circulation.
 - U. determine the existence or condition of polybutylene plumbing.
 - V. inspect or test for gas or fuel leaks, or indications thereof.
- 3.7. Electrical**
- I. The inspector shall inspect:
- A. the service drop;
 - B. the overhead service conductors and attachment point;
 - C. the service head, gooseneck and drip loops;
 - D. the service mast, service conduit and raceway;
 - E. the electric meter and base;
 - F. service-entrance conductors;
 - G. the main service disconnect;
 - H. panelboards and over-current protection devices (circuit breakers and fuses);
 - I. service grounding and bonding;

InterNACHI's International Standards of Practice for Performing a General Home Inspection

- J. a representative number of switches, lighting fixtures and receptacles, including receptacles observed and deemed to be arc-fault circuit interrupter (AFCI)-protected using the AFCI test button, where possible;
 - K. all ground-fault circuit interrupter receptacles and circuit breakers observed and deemed to be GFCIs using a GFCI tester, where possible; and
 - L. smoke and carbon-monoxide detectors.
- II. The inspector shall describe:
- A. the main service disconnect's amperage rating, if labeled; and
 - B. the type of wiring observed.
- III. The inspector shall report as in need of correction:
- A. deficiencies in the integrity of the service-entrance conductors' insulation, drip loop, and vertical clearances from grade and roofs;
 - B. any unused circuit-breaker panel opening that was not filled;
 - C. the presence of solid conductor aluminum branch-circuit wiring, if readily visible;
 - D. any tested receptacle in which power was not present, polarity was incorrect, the cover was not in place, the GFCI devices were not properly installed or did not operate properly, evidence of arcing or excessive heat, and where the receptacle was not grounded or was not secured to the wall; and
 - E. the absence of smoke detectors.
- IV. The inspector is not required to:
- A. insert any tool, probe or device into the main panelboard, sub-panels, distribution panelboards, or electrical fixtures.
 - B. operate electrical systems that are shut down.
 - C. remove panelboard cabinet covers or dead fronts.
 - D. operate or re-set over-current protection devices or overload devices.
- E. operate or test smoke or carbon-monoxide detectors or alarms
 - F. inspect, operate or test any security, fire or alarms systems or components, or other warning or signaling systems.
 - G. measure or determine the amperage or voltage of the main service equipment, if not visibly labeled.
 - H. inspect ancillary wiring or remote-control devices.
 - I. activate any electrical systems or branch circuits that are not energized.
 - J. inspect low-voltage systems, electrical de-icing tapes, swimming pool wiring, or any time-controlled devices.
 - K. verify the service ground.
 - L. inspect private or emergency electrical supply sources, including, but not limited to: generators, windmills, photovoltaic solar collectors, or battery or electrical storage facility.
 - M. inspect spark or lightning arrestors.
 - N. inspect or test de-icing equipment.
 - O. conduct voltage-drop calculations.
 - P. determine the accuracy of labeling.
 - Q. inspect exterior lighting.

3.8. Fireplace

- I. The inspector shall inspect:
- A. readily accessible and visible portions of the fireplaces and chimneys;
 - B. lintels above the fireplace openings;
 - C. damper doors by opening and closing them, if readily accessible and manually operable; and
 - D. cleanout doors and frames.
- II. The inspector shall describe:
- A. the type of fireplace.

InterNACHI's International Standards of Practice for Performing a General Home Inspection

III. The inspector shall report as in need of correction:

- A. evidence of joint separation, damage or deterioration of the hearth, hearth extension or chambers;
- B. manually operated dampers that did not open and close;
- C. the lack of a smoke detector in the same room as the fireplace;
- D. the lack of a carbon-monoxide detector in the same room as the fireplace; and
- E. cleanouts not made of metal, pre-cast cement, or other non-combustible material.

IV. The inspector is not required to:

- A. inspect the flue or vent system.
- B. inspect the interior of chimneys or flues, fire doors or screens, seals or gaskets, or mantels.
- C. determine the need for a chimney sweep.
- D. operate gas fireplace inserts.
- E. light pilot flames.
- F. determine the appropriateness of any installation.
- G. inspect automatic fuel-fed devices.
- H. inspect combustion and/or make-up air devices.
- I. inspect heat-distribution assists, whether gravity-controlled or fan-assisted.
- J. ignite or extinguish fires.
- K. determine the adequacy of drafts or draft characteristics.
- L. move fireplace inserts, stoves or firebox contents.
- M. perform a smoke test.
- N. dismantle or remove any component.
- O. perform a National Fire Protection Association (NFPA)-style inspection.

- P. perform a Phase I fireplace and chimney inspection.

3.9. Attic, Insulation & Ventilation

I. The inspector shall inspect:

- A. insulation in unfinished spaces, including attics, crawlspaces and foundation areas;
- B. ventilation of unfinished spaces, including attics, crawlspaces and foundation areas; and
- C. mechanical exhaust systems in the kitchen, bathrooms and laundry area.

II. The inspector shall describe:

- A. the type of insulation observed; and
- B. the approximate average depth of insulation observed at the unfinished attic floor area or roof structure.

III. The inspector shall report as in need of correction:

- A. the general absence of insulation or ventilation in unfinished spaces.

IV. The inspector is not required to:

- A. enter the attic or any unfinished spaces that are not readily accessible, or where entry could cause damage or, in the inspector's opinion, pose a safety hazard.
- B. move, touch or disturb insulation.
- C. move, touch or disturb vapor retarders.
- D. break or otherwise damage the surface finish or weather seal on or around access panels or covers.
- E. identify the composition or R-value of insulation material.
- F. activate thermostatically operated fans.
- G. determine the types of materials used in insulation or wrapping of pipes, ducts, jackets, boilers or wiring.
- H. determine the adequacy of ventilation.

InterNACHI's International Standards of Practice for Performing a General Home Inspection

3.10. Doors, Windows & Interior

I. The inspector shall inspect:

- A. a representative number of doors and windows by opening and closing them;
- B. floors, walls and ceilings;
- C. stairs, steps, landings, stairways and ramps;
- D. railings, guards and handrails; and
- E. garage vehicle doors and the operation of garage vehicle door openers, using normal operating controls.

II. The inspector shall describe:

- A. a garage vehicle door as manually-operated or installed with a garage door opener.

III. The inspector shall report as in need of correction:

- A. improper spacing between intermediate balusters, spindles and rails for steps, stairways, guards and railings;
- B. photo-electric safety sensors that did not operate properly; and
- C. any window that was obviously fogged or displayed other evidence of broken seals.

IV. The inspector is not required to:

- A. inspect paint, wallpaper, window treatments or finish treatments.
- B. inspect floor coverings or carpeting.
- C. inspect central vacuum systems.
- D. inspect for safety glazing.
- E. inspect security systems or components.
- F. evaluate the fastening of islands, countertops, cabinets, sink tops or fixtures.
- G. move furniture, stored items, or any coverings, such as carpets or rugs, in order to inspect the concealed floor structure.
- H. move suspended-ceiling tiles.
- I. inspect or move any household appliances.

- J. inspect or operate equipment housed in the garage, except as otherwise noted.
- K. verify or certify the proper operation of any pressure-activated auto-reverse or related safety feature of a garage door.
- L. operate or evaluate any security bar release and opening mechanisms, whether interior or exterior, including their compliance with local, state or federal standards.
- M. operate any system, appliance or component that requires the use of special keys, codes, combinations or devices.
- N. operate or evaluate self-cleaning oven cycles, tilt guards/latches, or signal lights.
- O. inspect microwave ovens or test leakage from microwave ovens.
- P. operate or examine any sauna, steam-generating equipment, kiln, toaster, ice maker, coffee maker, can opener, bread warmer, blender, instant hot-water dispenser, or other small, ancillary appliances or devices.
- Q. inspect elevators.
- R. inspect remote controls.
- S. inspect appliances.
- T. inspect items not permanently installed.
- U. discover firewall compromises.
- V. inspect pools, spas or fountains.
- W. determine the adequacy of whirlpool or spa jets, water force, or bubble effects.
- X. determine the structural integrity or leakage of pools or spas.

*InterNACHI's International Standards of Practice for Performing a General Home Inspection***4. Glossary of Terms**

- **accessible:** In the opinion of the inspector, can be approached or entered safely, without difficulty, fear or danger.
- **activate:** To turn on, supply power, or enable systems, equipment or devices to become active by normal operating controls. Examples include turning on the gas or water supply valves to the fixtures and appliances, and activating electrical breakers or fuses.
- **adversely affect:** To constitute, or potentially constitute, a negative or destructive impact.
- **alarm system:** Warning devices, installed or freestanding, including, but not limited to: carbon-monoxide detectors, flue gas and other spillage detectors, security equipment, ejector pumps, and smoke alarms.
- **appliance:** A household device operated by the use of electricity or gas. Not included in this definition are components covered under central heating, central cooling or plumbing.
- **architectural service:** Any practice involving the art and science of building design for construction of any structure or grouping of structures, and the use of space within and surrounding the structures or the design, design development, preparation of construction contract documents, and administration of the construction contract.
- **component:** A permanently installed or attached fixture, element or part of a system.
- **condition:** The visible and conspicuous state of being of an object.
- **correction:** Something that is substituted or proposed for what is incorrect, deficient, unsafe, or a defect.
- **cosmetic defect:** An irregularity or imperfection in something, which could be corrected, but is not required.
- **crawlspace:** The area within the confines of the foundation and between the ground and the underside of the lowest floor's structural component.
- **decorative:** Ornamental; not required for the operation of essential systems or components of a home.
- **describe:** To report in writing a system or component by its type or other observed characteristics in order to distinguish it from other components used for the same purpose.
- **determine:** To arrive at an opinion or conclusion pursuant to examination.
- **dismantle:** To open, take apart or remove any component, device or piece that would not typically be opened, taken apart or removed by an ordinary occupant.
- **engineering service:** Any professional service or creative work requiring engineering education, training and experience, and the application of special knowledge of the mathematical, physical and engineering sciences to such professional service or creative work as consultation, investigation, evaluation, planning, design and supervision of construction for the purpose of assuring compliance with the specifications and design, in conjunction with structures, buildings, machines, equipment, works and/or processes.
- **enter:** To go into an area to observe visible components.
- **evaluate:** To assess the systems, structures and/or components of a property.
- **evidence:** That which tends to prove or disprove something; something that makes plain or clear; grounds for belief; proof.
- **examine:** To visually look (see **inspect**).
- **foundation:** The base upon which the structure or wall rests, usually masonry, concrete or stone, and generally partially underground.
- **function:** The action for which an item, component or system is specially fitted or used, or for which an item, component or system exists; to be in action or perform a task.
- **functional:** Performing, or able to perform, a function.

InterNACHI's International Standards of Practice for Performing a General Home Inspection

- **functional defect:** A lack of or an abnormality in something that is necessary for normal and proper functioning and operation, and, therefore, requires further evaluation and correction.
- **general home inspection:** The process by which an inspector visually examines the readily accessible systems and components of a home and operates those systems and components utilizing this Standards of Practice as a guideline.
- **home inspection:** See **general home inspection**.
- **household appliances:** Kitchen and laundry appliances, room air conditioners, and similar appliances.
- **identify:** To notice and report.
- **indication:** That which serves to point out, show, or make known the present existence of something under certain conditions.
- **inspect:** To examine readily accessible systems and components safely, using normal operating controls, and accessing readily accessible areas, in accordance with this Standards of Practice.
- **inspected property:** The readily accessible areas of the buildings, site, items, components and systems included in the inspection.
- **inspection report:** A written communication (possibly including images) of any material defects observed during the inspection.
- **inspector:** One who performs a real estate inspection.
- **installed:** Attached or connected such that the installed item requires a tool for removal.
- **material defect:** A specific issue with a system or component of a residential property that may have a significant, adverse impact on the value of the property, or that poses an unreasonable risk to people. The fact that a system or component is near, at, or beyond the end of its normal, useful life is not, in itself, a material defect.
- **normal operating controls:** Describes the method by which certain devices (such as thermostats) can be operated by ordinary occupants, as they require no specialized skill or knowledge.
- **observe:** To visually notice.
- **operate:** To cause systems to function or turn on with normal operating controls.
- **readily accessible:** A system or component that, in the judgment of the inspector, is capable of being safely observed without the removal of obstacles, detachment or disengagement of connecting or securing devices, or other unsafe or difficult procedures to gain access.
- **recreational facilities:** Spas, saunas, steam baths, swimming pools, tennis courts, playground equipment, and other exercise, entertainment and athletic facilities.
- **report** (verb form): To express, communicate or provide information in writing; give a written account of. (See also **inspection report**.)
- **representative number:** A number sufficient to serve as a typical or characteristic example of the item(s) inspected.
- **residential property:** Four or fewer residential units.
- **residential unit:** A home; a single unit providing complete and independent living facilities for one or more persons, including permanent provisions for living, sleeping, eating, cooking and sanitation.
- **safety glazing:** Tempered glass, laminated glass, or rigid plastic.
- **shut down:** Turned off, unplugged, inactive, not in service, not operational, etc.
- **structural component:** A component that supports non-variable forces or weights (dead loads) and variable forces or weights (live loads).
- **system:** An assembly of various components which function as a whole.

InterNACHI's International Standards of Practice for Performing a General Home Inspection

- **technically exhaustive:** A comprehensive and detailed examination beyond the scope of a real estate home inspection that would involve or include, but would not be limited to: dismantling, specialized knowledge or training, special equipment, measurements, calculations, testing, research, analysis, or other means.
- **unsafe:** In the inspector's opinion, a condition of an area, system, component or procedure that is judged to be a significant risk of injury during normal, day-to-day use. The risk may be due to damage, deterioration, improper installation, or a change in accepted residential construction standards.
- **verify:** To confirm or substantiate.

These terms are found within the Standards of Practice. Visit InterNACHI's full Glossary online at <http://www.nachi.org/glossary.htm>

International Code of Ethics for Home Inspectors

The International Association of Certified Home Inspectors (InterNACHI) promotes a high standard of professionalism, business ethics and inspection procedures. InterNACHI members subscribe to the following Code of Ethics in the course of their business.

I. Duty to the Public

1. The InterNACHI member shall abide by the Code of Ethics and substantially follow the InterNACHI Standards of Practice.
2. The InterNACHI member shall not engage in any practices that could be damaging to the public or bring discredit to the home inspection industry.
3. The InterNACHI member shall be fair, honest and impartial, and act in good faith in dealing with the public.
4. The InterNACHI member shall not discriminate in any business activities on the basis of race, color, religion, sex, national origin, familial status, sexual orientation, or handicap, and shall comply with all federal,

state and local laws concerning discrimination.

5. The InterNACHI member shall be truthful regarding his/her services and qualifications.
6. The InterNACHI member shall not:
 - a. have any disclosed or undisclosed conflict of interest with the client;
 - b. accept or offer any disclosed or undisclosed commissions, rebates, profits, or other benefit from real estate agents, brokers, or any third parties having financial interest in the sale of the property; or
 - c. offer or provide any disclosed or undisclosed financial compensation directly or indirectly to any real estate agent, real estate broker, or real estate company for referrals or for inclusion on lists of preferred and/or affiliated inspectors or inspection companies.
7. The InterNACHI member shall not release any information about the inspection or the client to a third party unless doing so is necessary to protect the safety of others, to comply with a law or statute, or both of the following conditions are met:
 - a. the client has been made explicitly aware of what information will be released, to whom, and for what purpose, and;
 - b. the client has provided explicit, prior written consent for the release of his/her information.
8. The InterNACHI member shall always act in the interests of the client unless doing so violates a law, statute, or this Code of Ethics.
9. The InterNACHI member shall use a written contract that specifies the services to be performed, limitations of services, and fees.
10. The InterNACHI member shall comply with all government rules and licensing

InterNACHI's International Standards of Practice for Performing a General Home Inspection

requirements of the jurisdiction where he or she conducts business.

11. The InterNACHI member shall not perform or offer to perform, for an additional fee, any repairs or associated services to the structure for which the member or member's company has prepared a home inspection report for a period of 12 months. This provision shall not include services to components and/or systems that are not included in the InterNACHI Standards of Practice.

II. Duty to Continue Education

1. The InterNACHI member shall comply with InterNACHI's current Continuing Education requirements.
2. The InterNACHI member shall pass InterNACHI's Online Inspector Exam once every three years.

III. Duty to the Profession and to InterNACHI

1. The InterNACHI member shall strive to improve the home inspection industry by sharing his/her lessons and/or experiences for the benefit of all. This does not preclude

the member from copyrighting or marketing his/her expertise to other Inspectors or the public in any manner permitted by law.

2. The InterNACHI member shall assist the InterNACHI leadership in disseminating and publicizing the benefits of InterNACHI membership.
3. The InterNACHI member shall not engage in any act or practice that could be deemed damaging, seditious or destructive to InterNACHI, fellow InterNACHI members, InterNACHI employees, leadership or directors. Accusations of a member acting or deemed in violation of such rules shall trigger a review by the Ethics Committee for possible sanctions and/or expulsion from InterNACHI.
4. The InterNACHI member shall abide by InterNACHI's current membership requirements.
5. The InterNACHI member shall abide by InterNACHI's current message board rules.

Members of other associations are welcome to join InterNACHI, but a requirement of membership is that InterNACHI must be given equal or greater prominence in their marketing materials (brochures and websites) compared to other associations of membership.