



# Tape & Labels

Product	Polymer	Solids (%)	Viscosity (cps)	pH	Suggested Uses
Saitack® 258	Acrylic	68 to 70	4,500 to 5,500	8.0 to 9.0	Re-pulpable paper labels and tapes
Saitack® 267	Acrylic	45 to 48	1,500 to 3,000	6.5 to 8.5	Freezer grade label adhesives
Saitack® 283	Acrylic	55 to 57	600 to 1,000	7.5 to 8.5	Dry Bond Laminations
Saitack® 418	Acrylic	57 to 59	350 to 550	7.5 to 8.5	Economical labels needing moderate peel and shear strength to a variety of substrates
Saitack® 466P	Acrylic	55 to 57	1,000 to 1,300	7.0 to 8.0	Label adhesive with excellent water resistance and good adhesion to a wide variety of substrates. Suitable for thermal label applications.
Saitack® 514	Acrylic	58.0	5,000 to 13,000	8.5	Expanded polymer tapes including polyurethane, PVC and Polyethylene based foam tapes
Saitack® 566	Acrylic	48 to 50	1,200 to 1,800	7.0 to 9.0	Removable tape and label adhesive for filmic and paper facestocks



# Tape & Labels

Product	Polymer	Solids (%)	Viscosity (cps)	pH	Suggested Uses
Saitack® 678	Acrylic	49 to 51	1,000 to 2,000	6.5 to 9.0	Label adhesives with excellent clarity, water resistance and good adhesion to a wide variety of substrates.
Saitack® 926	Acrylic	59 to 61	2,000 to 3,000	7.0 to 9.0	Filmic label or formulating base for compounded pressure sensitive adhesives
Saitack® 934	Acrylic	68 to 70	4,000 to 7,000	3.5 to 4.5	Formulating Base for pressure sensitive and film laminating adhesives

## Description

STI Polymer is the partner of choice for your custom formulations of adhesives, paints and coatings. STI Polymer has built a reputation of proven performance, from providing manufacturers of paints and adhesives with the basic functional components of their formulations to producing private labeling of high-quality products for leading global corporations. STI's robust technical foundation and agility to meet the emerging needs, combined with an emphasis on long-term partnerships, drives its customers' successes.

## STI Polymer

You drive. We navigate.

Because we cannot anticipate nor control the many different conditions under which this information and our products may be used, we do not guarantee the applicability or the accuracy of this information or the suitability of our products in any given situation. Users of our product should make their own tests to determine the suitability of each such product for their particular purposes. The products discussed are sold without warranty, either express or implied, and the buyer assumes all responsibility for loss or damage arising from the handling or use of our products, whether done in accordance with directions or not. Also, statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent.

STI Polymer  
 5618 Clyde Rhyne Drive  
 Sanford, NC 27330  
 Phone: 800-874-5878  
 Fax: 919-777-6695  
 stipolymer.com