

GLOBOND composite panels specification:

SIZE FORM:

PRODUCTS NAME	SPECIFICATION				MOQ(m2)	Delivery lead time
	Length	Width	Thickness	Coil skin Thickness		
GLOBOND plus PVDF PANELS.	Standard: 2440mm. Option: Any length less than 1000mm.	Standard:1220mm. Option:1250mm. 1500mm.	Standard:4mm. Option:5mm.6mm.	Standard:0.50mm. Option:0.30mm.0.40mm.	600	15 days
GLOBOND FIREPROOF PANELS.	Standard: 2440mm. Option: Any length less than 1000mm.	Standard:1220mm. Option:1250mm. 1500mm.	Standard:4mm. Option:5mm.6mm.	Standard:0.50mm. Option:0.30mm.0.40mm.	600	15 days
GLOBOND POLYESTER PANELS.	Standard: 2440mm. Option: Any length less than 1000mm.	Standard:1220mm. Option:1250mm. 1500mm.	Standard:3mm. Option:2mm.5mm.6mm.	Standard:0.20mm. Option:0.10mm.0.30mm.	600	15 days
GLOBOND Stone finished panels.	Standard: 2440mm. Option: Any length less than 11000mm.	Standard:1220mm. Option:1250mm. 1500mm.	Standard:4mm. Option:3mm.5mm.6mm.	Standard:0.30mm. Option:0.40mm.0.50mm.	600	15 days
GLOBOND Wood finished panels.	Standard: 2440mm. Option: Any length less than 11000mm.	Standard:1220mm. Option:1250mm. 1500mm.	Standard:4mm. Option:3mm.5mm.6mm.	Standard:0.30mm. Option:0.40mm.0.50mm.	600	15 days
GLOBOND Brush finished panels.	Standard: 2440mm. Option: Any length less than	Standard:1220mm. Option:1250mm.	Standard:4mm. Option:3mm.5mm.6mm.	Standard:0.30mm. Option:0.40mm.0.50mm.	600	15 days

GLOBOND COMPOSITE PANELS



GLOBOND

	6000mm.	1500mm.				
GLOBOND Mirror finished panels.	Standard: 2440mm. Option:Any length less than 6000mm.	Standard:1220mm. Option:1250mm. 1500mm.	Standard:4mm. Option:3mm.5mm.6mm.	Standard:0.30mm. Option:0.40mm.0.50mm.	600	15 days
GLOBOND Spectra color panels.	Standard: 2440mm. Option:Any length less than 6000mm.	Standard:1220mm. Option:1250mm. 1500mm.	Standard:4mm. Option:3mm.5mm.6mm.	Standard:0.30mm. Option:0.40mm.0.50mm.	600	15 days
GLOBOND Stainless steel color panels.	Standard: 2440mm. Option:3200mm.4000mm.	Standard:1220mm. Option:600mm.1000mm. 1200mm.	Standard:4mm. Option:3mm.5mm.6mm.	Standard:0.30mm. Option:0.10mm.0.20mm.	300	25 days
GLOBOND Cooper composite panels.	Standard: 2440mm. Option:3200mm.4000mm.	Standard:1220mm. Option:600mm.1000mm. 1200mm.	Standard:4mm. Option:3mm.5mm.6mm.	Standard:0.30mm. Option: 0.20mm.	300	35 days
GLOBOND Zinc composite panels.	Standard: 2440mm. Option:3200mm.4000mm.	Standard:1220mm. Option:600mm.1000mm. 1200mm.	Standard:4mm. Option:3mm.5mm.6mm.	Standard:0.30mm. Option: 0.20mm.	300	45 days
GLOBOND Titanium composite panels.	Standard: 2440mm. Option:3200mm.4000mm.	Standard:1220mm. Option:600mm.1000mm. 1200mm.	Standard:4mm. Option:3mm.5mm.6mm.	Standard:0.30mm. Option: 0.20mm.	300	45 days
GLOBOND Shell Station	Standard: 2440mm. Option:Any length less than 6000mm.	Standard:1220mm. Option:1250mm. 1500mm.	Standard:4mm. Option:3mm.5mm.6mm.	Standard:0.30mm. Option:0.40mm.0.50mm.	600	15 days
GLOBOND MacDonal Store	Standard: 2440mm. Option:Any length less than	Standard:1220mm. Option:1250mm.	Standard:4mm. Option:3mm.5mm.6mm.	Standard:0.30mm. Option:0.40mm.0.50mm.	600	15 days

GLOBOND COMPOSITE PANELS



GLOBOND

	6000mm.	1500mm.				
GLOBOND Burgerking Store	Standard: 2440mm. Option: Any length less than 6000mm.	Standard: 1220mm. Option: 1250mm. 1500mm.	Standard: 4mm. Option: 3mm. 5mm. 6mm.	Standard: 0.30mm. Option: 0.40mm. 0.50mm.	600	15 days

REMARK:

1. The alloy 1100H18.3003H24.3105H24.5005H24.is available.
2. Most of the colors have two choice for interior and exterior.
3. The delivery lead time is base on the order quantity less than 10,000.00m2. if over than this quantity .pls check and confirm with the salesman.
4. The fireproof panels are in compliance with the following standard :
 - A. ASTM E84.
 - B. BS476 Part 6 and 7.
 - C. AS/NZS 1350.3.
 - D. EN13501.1.
 - E. DIN4102
 - F. NFPA285.

www.globond.com

GLOBOND COMPOSITE PANELS