

WATERZALL CONCENTRATE

General Purpose Cleaning Agent

1. Product Description

a. Basic Use: Waterzall Concentrate is a general purpose cleaning agent. It is formulated to be used at full strength for spot cleaning, or diluted with water for cleaning large areas or for clean-up of tools and equipment. Waterzall Concentrate dissolves and removes dirt, tacky film, spots, smudges and most unwanted deposits from floors, walls, doors, plastics, metal, rubber, fabric, carpeting and virtually any other surface. Use Waterzall Concentrate for clean-up of Diamite, Lexite, and Metco Epoxy Products.

b. Features/Benefits:

- Out-cleans most commonly found compounds even when diluted with water.
- Restores original color and brightness to the surface often eliminating the need for repainting.
- Non-abrasive cleaning agents will not mar or wear away the surface.
- Concentrate formula does not run, sag, drip or spread - even on vertical or overhead surfaces.
- Excellent for clean-up of tools and equipment used in epoxy coatings, grouts, and overlays.
- Neatly cleans up local spots without running or streaking.
- Swiftly and effectively removes grease, dirt and grime with virtually no effort.
- Safe to use on any surface or fabric with no harm to skin.
- Fresh fragrant cleaner leaves a deodorized scent.
- Non-flammable even in an open flame.
- Very economical when diluted with water.
- **c. Typical Applications:** Removes unhardened epoxy and urethane, greasy dirt, finger prints, pencil marks, ball point ink, wax, crayon, heel marks, grass stains, cooking grease, soap scum, smoke film, adhesive tape marks any grimy, greasy deposits of hard-to-remove matter.
- **d. Limitations:** Waterzall Concentrate may soften some unsound or porous painted surfaces.
- **e. Composition:** Waterzall Concentrate is a water-based emulsion cleaning agent designed to remove hydrocarbon based materials.

f. Color/Appearance: Waterzall Concentrate is amber in color with the consistency of a semi-fluid lotion.

2. Packaging

Waterzall Concentrate is packaged in 6 standard units:

Unit	Shipping Wt.
1-gal. (3.8 liter) jugs	57 lbs. (25.6Kg)
(6 per case)	
5-gal. (18.9 liter) pails	47 lbs. (21.3 Kg)
55-gal. (208 liter) drums	495 lbs. (224.5 Kg)

3. Estimating/Coverage

For general cleaning, 1 part of Waterzall Concentrate is mixed with 5 to 10 parts of water. Waterzall Concentrate may also be applied directly to heavily soiled areas.

4. Technical Data

Waterzall Concentrate is effective in removing and dissolving the following materials:

liquid epoxygreaseanimal fatvegetable oil

• ink • common dirt and grime

smoke filmpencil markswaxcrayon

5. Directions for Use

Spraying produces best results. Make sure sprayer is secure on spray bottle, and nozzle cap is screwed down tight. Hold sprayer six to eight inches from surface. Squeeze trigger firmly to spray, not squirt.

For general cleaning, make a solution using from 5 to 10 parts of water to 1 part of concentrate (depending upon nature of surface and density of soil). Apply the solution with spray, sponge or cloth - and wipe the area clean.

For local spots of heavy dirt, smudges, pencil marks, wax, etc., spray a light film of Waterzall Concentrate over the soiled area. Then rub away dirt and grime with a few light strokes of a damp sponge and rinse thoroughly with plain water.

Metalcrete Industries

For removing grease spots, grass stains, etc. from clothing or other fabrics, spray with Waterzall Concentrate and rub it into the fibers of the cloth. Allow time for the material to penetrate the fabric thoroughly, then rinse with tap water until the area is completely clean.

6. Availability

Waterzall Concentrate is normally available immediately from your local distributor or it will be shipped within 5 working days upon receipt of order. Please contact your local Metalcrete representative or call Metalcrete directly for more information.

7. Warranty

Waterzall Concentrate is manufactured in strict accordance with the quality control standards of Metalcrete Industries. It is guaranteed to perform as indicated on this data sheet when applied by competent applicators.

8. Technical Service

Metalcrete technical service representatives are available to provide on-site assistance with a minimum three day notice.

Metalcrete Industries 4133 Payne Avenue • Cleveland, Ohio 44103 440-526-5600 • 800-526-5602 • FAX 440-526-5601

MT 1007:6/08www Printed in U.S.A.